



GENERAL NOTES

BRAKETS TO BE GALVANIZED BEFORE FINAL MACHINE ROPE CLAMP PC 39, TO BE POSITIONED AT ASSEMBLY WITH WINCH SO THAT WITH THE REEFER IN FULL OPEN POSITION THE WINCH WILL BE THE CENTER OF THE MOUNTING BRKT (WITH TWO DEAD TURNS ON EACH LINE)

1. PART HAS MARKED THIS (X) ARE LISTED FOR INFORMATION ONLY. ITEMS NOT FOUND ON THIS FL ARE DETAILED ON BRKT 2.
2. ALL 97° ANGLES ON DRAWINGS APPLY TO PLATE C HOLE

REFERENCES		DRAWING NO.	
NO.		DATE OF REV.	BY
1.	RAMP HOISTING - ARREST		
2.	RAMP HOISTING - DETAILS - SHT. 2	LEVP	10
3.	RAMP AND ATTACHMENTS	LEVP	10
4.	RAMP SAFETY LATCH	LEVP	10

NAVY DEPARTMENT		WASHINGTON, D. C.	
EXAMINED OFFICIAL: _____ SIGNATURE: _____ NAME: _____ TITLE: _____ DATE: _____ TIME: _____ PLACE: _____ METHOD: _____ RESULT: _____ REMARKS: _____ APPROVED: _____ DATE: _____ TIME: _____ PLACE: _____ METHOD: _____ RESULT: _____ REMARKS: _____		BUREAU OF SHIPS 36 FOOT LCVP MARK (3) RAMP HOISTING DETAILS (SHEET 1) BUREAU OF SHIPS NO. _____ SCALE: AS SHOWN H 1098020	
CONTRACT DRAWING		LCVP	