

[illegible][illegible]

- ## GENERAL NOTES

1. FOR DESCRIPTION OF MATERIALS SEE CONTRACT SPECIFICATIONS.
2. THE BATTERY BOX FOR ENGINE STARTING BATTERIES SHALL BE PROVIDED WITH A SUITABLE DRIPPROOF COVER.
3. PAINTING:
- (A) PAINTING OF ELECTRICAL CABLES AND APPLIANCES SHALL BE IN ACCORDANCE WITH GENERAL SPECIFICATIONS SUBSECTION 510-1.
- (B) ALL INSTRUMENT WIRING TERMINALS SHALL BE GIVEN TWO COATS OF INSULATING VARNISH AFTER ASSEMBLY. INSULATING VARNISH SHALL BE IN ACCORDANCE WITH MIL SPEC 13023A, TYPE I, GRADE A.
4. THE DROP IN VOLTAGE ON ANY PART OF THE ELECTRICAL INSTALLATION OF THIS BOAT SHALL NOT EXCEED 5 PERCENT OR 0.6 VOLT. THE MINIMUM ALLOWABLE VOLTAGE SHALL BE 12.0 VOLTS.
5. ADDITIONAL WIRING, FITTINGS, OUTLETS AS MAY BE REQUIRED TO SUIT THE ACTUAL APPROVED INSTALLATION OR TO COVER ANY INADEQUACIES OR OTHER DEFICIENCIES SHALL BE PROVIDED AND INSTALLED BY THE CONTRACTOR.
6. THIS PLAN DEVELOPED FOR USE WITH GRAY MARINE DIESEL ENGINE WITH 30 HP, 1 CY, D.O.G. GENERATOR.
7. FOR READY IDENTIFICATION PURPOSES OF ELECTRICAL CIRCUITS ALL CABLES SHALL BE COLOR Banded AS NOTED HEREAFTER. COLOR BAND TWO INCHES WIDE TO BE PAINTED ON THE EXTERIOR OF ELECTRICAL EQUIPMENT AT POINT OF ENTRANCE. THE COLOR BANDING SCHEME SHALL BE AS FOLLOWS:
- ① DRIP - 4 - BLACK      ④ TRIP - 14 - BLUE      ⑦ DRIP - 4 - YELLOW
- ② DRIP - 4 - GREEN      ⑤ TRIP - 14 - BLUE      ⑧ DRIP - 4 - GREEN
- ③ DRIP - 4 - BLACK      ⑥ TRIP - 14 - RED
- THE CONTRACTOR SHALL USE ENAMEL IN ACCORDANCE WITH THE REQUIREMENTS OF GENERAL SPECIFICATIONS APPENDIX 6 DATED JUNE 1943.

DRAWN BY: D. D. Bunch  
 TRACED BY: Indra Walader  
 EXAMINED BY: C. B. John  
 IN CHARGE: C. B. John

T. E. Casner  
 HEAD ENGINEER  
 DATE July 12, 1964

36 FT. LANDING CRAFT  
LCP(R)

ELECTRICAL PLAN  
SCALE - NONE

NAVY DEPARTMENT  
BUREAU OF SHIPS

WASHINGTON, D.C. MAY 4, 1944

Carl M. Dalton  
FOR CHIEF OF BUREAU

BUREAU OF SHIPS NUMBER

LCP(R)		8935
--------	--	------